



0-420-12 - 21.5" Driving Worklamp Bar with Position and Amber Warning

Durite Worklight 21.5" Driving Lamp with Amber Warning LED's and Position Lamp. 12/24V. 200W OSRAM LED, 16,800 Lumens (5551 Effective). 1703 LUX at 10M. 5700k Colour Temperature. IP68/IP69k. PC Lens, Aluminium Housing, SS304 Brackets. 60cm Fly Lead with 6PIN DT Connector. Size: 560.6*70*67.3mm. E Marked R10 (EMC), R7 (DRL), R112 (Driving) and R65 (Warning).

Fly Leads:

- Red = Main Driving Light
- Black = Negative -VE
- Grey = White Position Light
- Yellow = Amber Warning Light
- Green = Amber Position Light



THE TRUSTED QUALITY BRAND FOR PROFESSIONALS

TECHNICAL SPECIFICATIONS

Type	Worklight Driving Lamp with Position / Amber Warning
Voltage	10-30VDC
LED's	Driving: 40 x 5W OSRAM LED, Pos 30 LED's Amber 40 LED's
Power	Driving: 84W, Pos 1W, Warning 11W Amber
Current Draw	Driving 6.5A at 12V. Pos 0.15A at 12V, Warning 0.77A at 12V
Lumens / Lux	16,800 (5551 Effective). 1703 LUX at 10M
IP Rating	IP68 / IP69K
Material Construction	Aluminium with PC Lens. Bracket SS304
Weight	2.355Kg
Dimensions	560.6*70*67.3mm
Operating Temperature	-30°C to +65°C
Storage Temperature	-40°C to +85°C
Certificate	CE, E Mark R10, R7, R65, R112

TECHNICAL DRAWING

