

# 11 Series

## Low-Profile Signal Lighting



Part#	Description	EAN Code
11AM	Rear Indicator Lamp, Amber Lens	9335962035885
11ACM	Rear Indicator Lamp, Clear Lens	9335962035922
11CAT1M	Front Indicator Lamp, Clear Lens	9335962036011
11FM	Rear Fog Lamp, Red Lens	9335962035915
11FCM	Rear Fog Lamp, Clear Lens	9335962035946
11RM	Stop / Tail Lamp, Red Lens	9335962035892
11RCM	Stop / Tail Lamp, Clear Lens	9335962035939
11WM	Reverse Lamp, Clear Lens	9335962035908

<b>Voltage</b>	9-32V
<b>Dimensions</b>	89 x 30 x 8mm
<b>IP rating</b>	IP67
<b>Warranty</b>	5 Years
<b>Cable</b>	250mm (stripped-end)
<b>Operating temperature</b>	-30°C to +50°C
<b>Current draw (13.8V / 28V)</b>	<b>Indicator:</b> 0.07A / 0.05A, <b>Stop:</b> 0.05A / 0.04A, <b>Tail:</b> 0.01A / 0.01A, <b>Fog:</b> 0.19A / 0.1A, <b>Reverse:</b> 0.05A / 0.04A

ECE approval	Function	Approval#
	Rear Indicator (R6)	2a-E9-01.23077
	Front Indicator (R6-C1)	1-E9-01.22585
	Stop / Tail (R7)	R1-S1-E9-02.23529
	Fog (R38)	F1-E9-00.22163
	Reverse (R23)	AR-E9-00.22216

Wiring colour codes	YELLOW: Indicator [+]	BLUE: Fog [+]
	RED: Stop [+]	BROWN: Tail [+]
	BLACK: Reverse [+]	WHITE: Earth [-]

**⚠ Installation to be undertaken by a competent professional**

### 3M™ ADHESIVE EASY MOUNTING SYSTEM

Ensure mounting surface is flat, clean and dry prior to installation.

1. Peel the protective layer from one side of the mounting pad and fix to the rear of the lamp, aligning the breather holes.
2. Peel off the remaining protective layer, feed the wires through the hole in the vehicle surface and firmly press the lamp to fix into position.
3. Use screws for additional security if required.



11RM / 11FM



11AM



Clear Lens Options

