

	REVISION HISTORY								
REV.	DESCRIPTION	DATE							
D	LABEL (990.315) REMOVED AS PER CR VA0234	05-Jun-06							
E	UPDATED AS PER CR# VA 0407	2007-11-22							
F	REVISE PER VLM1337	2015-09-01							



TOP VIEW



CUSTOMER COPY

ISOMETRIC VIEW

FRONT VIEW

NOTES:
1. DIMENSIONS IN MILLIMETERS [INCHES (FOR REFERENCE)]
2. USE SUB ASSEMBLY (100-407.000) FOR MANUFACTURE

NON DISCLOSURE AGREEMENT								
THIS DRAWING AND THE DESIGN IT DISCLOSES ARE THE PRIVATE PROPERTY OF ECCO AND IS ISSUED IN CONFIDENCE FOR ENGINEERINGINFORMATION VLY. THE DRAWING AND / OR DESIGN MAY NOT BE USED, COPIED, REPRODUCED, OR OTHERWISE DISCLOSED IN PART OR AS A WHOLE TO OUTSIDERS C								
SED FOR ANY OTHER PURPOSE WITHOUT THE PRIOR WRITEN CONSENT OF ECCO. THE DRAWING IS SUBJECT TO RECALL AT ANY TIME. YOUR POSSESSION OF THIS DOCUMENT CONSTITUTES ACCEPTANCE OF THES FERMS © 2012 FCCO.	4							

SCALE 1:3			APP	ROVALS	DATE					European Division +44 (0) 113 237 5340	
CAD GENERATED DRAWING			DRAWN BY	MDG	2015-03-23		3		Vict	oria Industrial Park, Victo Seacroft, Leeds LS142	ria Road, 2LA
DO NOT MANUALLY UPDATE. MODEL REFERENCED:Y		CHECKED	MPS	2015-05-21		2 F	ROUP	м	Tel: +44 (0)113 237 53 Fax: +44 (0)113 237 53		
TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES ARE:		MECH. ENG.	ССМ	2015-05-22		-			www.eccogroup.co	m	
MILLIMETERS DECIMALS	INCHES DECIMALS	ANGLES ± 0.5	ELEC. ENG.			BEACO	N, 400	SERIES, MA	G 50	, AMBER, LES	S BULB
XX. ± 1.0mm XX.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	ERACTIONS	TEST ENG.	ALM	2015-05-21	CUSTOMER PAR		407.000		PRODUCT SERIES: 400 Series Be	eacon
THIRD ANGLE PROJECTION		SALES.									
					^{SIZE:} A	DWG. N	0. 4	07.0	00	REV.	
		Electronically Controlled Use Latest Copy		SHEET 1 OF 1	Project: C	R VA0065	Date Cre	eated: 04-Jun-04	F		

SPECIFICATIONS

1. CERTIFICATIONS; R10 & R65 APPROVED 2. FLASH MODE: MAXIMUM 160 FPM 3. VOLTAGE (NOMINAL): 12VDC 4. VOLTAGE (EXTREME):13.5VPC 5. CURRENT (MAXIMUM): 4 SAMPS 6. POWER (MAXIMUM): 4 SAMPS 6. POWER (MAXIMUM): 5 WATTS 7. TEMPERATURE AND E: -30 C TO 50 C 8. CONNECTION 13 AWG WIRES IN A CABLE 9. MOUNTING 14G 50 10. BASE MATERIAL: POLYCARBONATE 11. LENS MATERIAL: POLYCARBONATE

11. LENS MATERIAL: POLYCARBC 12. PRODUCT WEIGHT: 1.00 KG