

LPB SERIES

Low-Profile Warning Beacons



Part#	Description	EAN Code
LPBR65A	Amber Lens Warning Beacon, Fixed Mount	9335962036219
LPBR65A-MM	Amber Lens Warning Beacon, Magnetic Mount	9335962036226
LPBR65C	Clear Lens Warning Beacon, Fixed Mount	9335962036233
LPBR65C-MM	Clear Lens Warning Beacon, Magnetic Mount	9335962036240

Voltage	12/24V
Dimensions	Ø148 x 55
IP rating	IP67
Warranty	3 Years
Cable	Fixed Mount: 400mm (stripped-end) Magnetic Mount: 3m coiled cable with cigar plug
Current draw (13.8V / 28V)	2A max.

ECE approval	Function	Approval#
	ECE R65	TA1-00-E9-6489
	ECE R10.06	10R-06-E9-22260

Wiring colour codes	RED: Power [+]	GREEN: Pattern Select [+]	BLUE: Earth [-]
	To select pattern apply GREEN to RED wire:		
	<ul style="list-style-type: none"> • less than 1 second for next flash pattern • approx. 2-3 seconds to return to default flash pattern 		
	Connect GREEN wires of multiple beacons together for synchronisation - all beacons must be set to the same flash pattern.		

Flash pattern list	Single	125FPM (R65)
	Quad	125FPM
	Burst	1200FPM
	Rotate 1	75FPM
	Rotate 2	100FPM

Mounting instructions	<p>⚠ Installation to be undertaken by a competent professional</p> <p>⚠ Magnetic beacon designed for use on stationary vehicles only</p>
	<p>Fixed mount: Fix using bolts supplied</p> <p>Magnetic Mount: Affix to clean, flat surface parallel to the ground.</p> <p>Magnetic beacon designed for use on stationary vehicles only - use on moving vehicles is the sole responsibility of the user.</p> <p>This magnetic beacon has been tested at speeds not exceeding 100km/h.</p>



LPBR65A



LPBR65A-MM



LPBR65C



LPBR65C-MM

