



0-421-29 - 9" LED High Beam, Position and Warning Lamp

Durite 9" High Beam, Position and Warning Lamp with DT Connector. 10-30V. 82W, Diecast black graphene housing, PC Lens with stainless steel SS304 bracket. IP66, IP69K About 50,000 hours life time. 6000 Raw Lumens. 1 LUX at 275 Metres. 5700-6500k.

E Marked R148, R65 and R10.05 EMC.

Fly Leads:

Red = High Beam

Yellow = Amber Position Lamp

Blue = White Position Lamp

Green = Warning Light

White = Sync

Black = Earth -VE

Cable Specification		
NO.	Color	Function
1	Red	High Beam +
2	Black	Ground -
3	Blue	Position (W) +
4	Yellow	Position (Y) +
5	Green	Strobe +
6	White	Synchronizing



THE TRUSTED QUALITY BRAND FOR PROFESSIONALS

TECHNICAL SPECIFICATIONS

Type	9" High Beam / Position / Warning Lamp
Voltage	10-30VDC
LED's	12 x 5W LED: High beam: 60W 40 x 0.1W LED: Position beam: 4W, 9 x 2W LED Warning 18W
Power	82W Max
Current Draw 24V	High Beam: 1.38A, Position 0.16A, Warning 0.63A
Illuminance	6000 Raw / 1700 Effective Lumens. 1 LUX at 275Metres
IP Rating	IP66, IP69K
Material Construction	Graphene with PC Lens. Bracket SS304
Weight	1.5Kg
Dimensions	Please see below
Operating Temperature	-40°C ~ + 50°C
Storage Temperature	-40°C ~ + 50°C
Certificate	CE, E Mark, R148, R65, R10 EMC

TECHNICAL DRAWING

