

385 SERIES

Rear Combination Lamps




Part#	Description	EAN Code
385ARRMB	Stop / Tail / Indicator, Boxed	9335962036349
385ARWML	Stop / Tail / Indicator / Reverse, Left Lamp, Boxed	9335962036356
385ARWMR	Stop / Tail / Indicator / Reverse, Right Lamp, Boxed	9335962036370
385FWARM	Stop / Tail / Indicator / Reverse / Fog, Blister Pack	9335962036448

Voltage	9-32V
Dimensions	387 x 105 x 31mm
IP rating	IP67
Warranty	5 Years
Cable	400mm (stripped-end)
Operating temperature	-30°C to +50°C
Current draw (13.8V / 28V)	Stop: 0.23A / 0.12A, Tail: 0.57A / 0.30A, Indicator: 0.24A / 0.14A, Fog: 0.34A / 0.19A, Reverse: 0.37A / 0.19A

ECE approval	385ARRMB	385ARWM-	385FWARM
	Tail (R7) - R1-E9-02.23585	Tail (R7) - R1-E9-02.23586	Tail (R7) - R1-E9-02.23848
	Stop (R7) - S1-E9-02.23585	Stop (R7) - S1-E9-02.23586	Stop (R7) - S1-E9-02.23848
	Ind. (R6) - 2a-E9-01.23585	Ind. (R6) - 2a-E9-01.23586	Ind. (R6) - 2a-E9-01.23848
		Rev. (R23) - AR-E9-00.23586	Fog (R38) - F1-E9-00.23848
			Rev. (R23) - AR-E9-00.23848



Inactive



Active - 385ARRMB



Active - 385ARWM-



Active - 385FWARM

Wiring colour codes	BROWN: Tail [+]	YELLOW / GREEN: Indicator [+]
	RED: Stop [+]	BLUE: Fog [+]
	BLACK: Reverse [+]	WHITE: Earth [-]

Mounting instructions	⚠ Installation to be undertaken by a competent professional
	<ol style="list-style-type: none"> 1. Separate the base plate from the lamp and horizontally mount onto a flat surface using the fixings provided. 2. Run wire through hole in fixing surface then re-align the lamp and clip into the mounting base using light pressure to ensure it sits in place correctly - ensuring the arrow on the lens is pointing outwards of the vehicle.

