

| REVISION HISTORY | | | | | | | | |
|------------------|--|------------|--|--|--|--|--|--|
| REV. | DESCRIPTION | DATE | | | | | | |
| Е | LABEL (990.315) REMOVED AS PER CR VA0234 | 02-Jun-06 | | | | | | |
| F | UPDATED AS PER CR# VA 0407 | 2007-11-21 | | | | | | |
| G | REVISE PER LC0004 | 2015-08-17 | | | | | | |
| | | | | | | | | |

CUSTOMER COPY




TOP VIEW



FRONT VIEW

| NOTES 1. 2. | S: DIMENSIONS IN MILLIMETERS[INCHES (FOR REFERENCE)] USE SUB ASSEMBLY (100-403.001) FOR MANUFACTURE | |
|--------------------------|--|---|
| | NON DISCLOSURE AGREEMENT | Í |
| ONLY. THE DRAW | A NO THE DESIGN IT DISCLOSES ARE THE PRIVATE PROPERTY OF ECCO AND IS ISSUED IN CONFIDENCE FOR ENGINEERINGINFORMATION ING AND / OR DESIGN MAY NOT BUESD, COPIED, ERPRODUCED, OR OTHERWISE DECLOSED IN PART OR AS A WHOLE TO OUTDISEES CO OTHER PURPOSE WITHOUT HE PRIOR WRITHIN CONSENT OF ECCO. THE DRAWING IS SUBJECT TO RECALL AT ANY TIME, YOUR POSSESSION OF THIS DOCUMENT CONSTITUETS ACCEPTANCE OF THESE TERMS, © 2012 ECCO | |

| SCALE 1:3 | | | APP | ROVALS | DATE | E | | A | | | European Division +44 (0) 113 237 534 | 0 |
|--|--|-----------------|---|---------|------------|-------|------------------------|-----|---------------------------------------|------------------|--|----|
| CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED:A | | | DRAWN BY | MPS | 2015-03-23 | | \gtrsim | Z | [[[] [] [] [] [] [] [] [] [| | toria Industrial Park, Victo Seacroft, Leeds LS14 | |
| | | | CHECKED | MPS | 2015-05-21 | | R | ð | GROUF | ∋™ | Tel: +44 (0)113 237 53 Fax: +44 (0)113 237 5 | |
| TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES ARE: | | | MECH. ENG. | ССМ | 2015-05-26 | | | - | | | www.eccogroup.co | |
| MILLIMETERS DECIMALS | INCHES DECIMALS | ANGLES ± 0.5 | ELEC. ENG. | | | | BEA | ACC | N. 4 SERIES | 5, 3 BL | T,AMBER, 12 | 2V |
| XX. ± 1.0mm XX.X ± 0.5mm | X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02 | FRACTIONS | TEST ENG. | ALM | 2015-03-23 | CUSTO | | | | PRODUCT SERIES: | | |
| | | ± 1/64 | SALES. | 403.001 | | | 400 Series Beacon | | | | | |
| | | | | | SIZE: | А | DWG | NO. | 403.0 | 01 | REV. | |
| | | Electroni | Electronically Controlled Use Latest Copy | | SHEET | | Project: CR VA0065 Dat | | Date Cr | eated: 26-Jul-04 | G | |



ISOMETRIC VIEW

SPECIFICATIONS

1. CERTIFICATIONS; R10 & R65 APPROVED 2. FLASH MODE: MAXIMUM 185 FPM 3. VOLTAGE (NOMINAL): 12VDC 4. VOLTAGE (EXTREME): 13.5 VDC 5. CURRENT (MAXIMUM): 4.6 AMPS 6. POWER (MAXIMUM): 56 WATTS 7. TEMPERATURE RANGE: -30 C TO 50 C 8. CONNECTION:18 AWG WIRES IN A CABLE 9. MOUNTING: 3 BOLT 10. BASE MATERIAL: POLYCARBONATE 11. LENS MATERIAL: POLYCARBONATE 12. PRODUCT WEIGHT: 1.00 KG