

	REVISION HISTORY							
REV.	DESCRIPTION							
D	UPDATED AS PER VA CR 1697	2014-01-07						
D	REVISE PER VA CR 1697	2014-05-12						
Е	REVISED PER LC1277	2019-02-18						





SPECIFICATIONS:

1. CERTIFICATIONS; UN ECE R10 APPROVED

Note: Unique components, accessories and hardware kits are not typically Included in the product certification test protocols. Unless otherwise Specified, the product certification referred to herein are predicated Upon The base product model configuration.

- 2. FLASH MODE: HEX FLASH PATTERN (60 FPM)
- 3. VOLTAGE (NOMINAL): 12/24v DC
- 4. VOLTAGE (EXTREME): 10 to 32v DC
- 5. CURRENT (RMS): 0.2A (@ 10 VDC NOMINAL)
- 6. CURRENT (PEAK): 0.35A (@ 10 VDC NOMINAL)
- 7. POWER (RMS MAXIMUM): 2.5W (@ 24 VDC NOMINAL)
- 8. TEMPERATURE RANGE: -20°C TO 50°C
- 9. CONNECTION: RED (POSITIVE), BLACK (NEGATIVE)
- 10. MOUNTING: 1 BOLT
- 11. BASE MATERIAL: POLYCARBONATE
- 12. LENS MATERIAL: POLYCARBONATE
- 13. PRODUCT WEIGHT: 0.8KG APPROX

NOTES:

. DIMENSIONS IN MILLIMETERS [INCHES(FOR REFERENCE)]

ON DISCLOSURE ACREEMENT

IS DRAWING AND THE DESIGN IT DISCLOSES ARE THE PRIVATE PROPERTY OF ELECTRONIC CONTROLS CO. AND IS ISSUED IN CONFIDENCE FOR ENGINEERING INFORMATION ONLY, TH DRAWING AND / OR DESIGN MAY NOT BE USED, COPIED, REPRODUCED, OR OTHERWISE DISCLOSED IN PART OR AS A WHOLE TO OUTSIDERS OR USED FOR ANY OTHER PURPOSE WITHOUT THE PROFO WRITTEN CONSENT OF ELECTRONIC CONTROLS CO. 11HE DRAWING IS SUBJECT TO RECALL AT ANY TIME, YOUR POSSESSION OF THIS DOCUMENT CONSTITUTES

	SCALE 1:3			APP	ROVALS	DATE						
CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED: C			DRAWN BY 2017-09-08			ECCO ® www.eccolink.com						
			CHECKED	LSH	2017-09-20	*						
		TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:		MECH. ENG.	JGW	2017-09-14	Americas (800) 635-5900 Europe +44 (0)113 237 5340 Asia Pacific +61 (0)3 6332244					
ſ	MILLIMETERS DECIMALS	INCHES DECIMALS X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02 RD ANGLE PROJECTIO	ANGLES ± 0.5*	ELEC. ENG.	RMF	2017-09-25	BEA	CON, 400, 1 BOL	Γ, LED, 🗚	AMBER, 12/24\	V	
	XX. ± 1.0mm XX.X ± 0.5mm		X.XX ± 0.04	FRACTIONS	TEST ENG.	DFG	2017-09-18	CUSTOMER PAR			PRODUCT SERIES:	
+	TLII		± 1/64	SALES.	JSM	2018-06-05	5L1.20)4		400		
1	A LOSE TROSECTION		1				SIZE: A4	DWG. NO.	5L1.2	204	REV.	
	7			Electronically Controlled Use Latest Copy			SHEET 1 OF 1	Project: 10004	Date Cr	eated: 09-Jun-04]	