



REVISION HISTORY								
REV.	DESCRIPTION							
02	REVISED PER LC1492	2018-04-11						
Α	INITIAL RELEASE PER LC1492	2018-05-22						
В	REVISED PER LC2445	2020-03-23						

SPECIFICATIONS

1. CERTIFICATIONS: R10 & R65 APPROVED

Note: Unique components, accessories and hardware kits are not typically Included in the product certification test protocols. Unless otherwise Specified, the product certification referred to herein are predicated Upon the base product model configuration.

- 2. FLASH MODE: DEFAULT 125 FPM DOUBLE FLASH
- 3. VOLTAGE (NOMINAL): 12-24 VDC
- 4. VOLTAGE (EXTREME): 10-32 VDC
- 5. CURRENT (PEAK): 1.40A (@ 12 VDC NOMINAL)
- 6. POWER (MAXIMUM): 17W (@ 12 VDC NOMINAL)
- 7. TEMPERATURE RANGE: -30°C (-22°F) TO 50°C (122°F)
- 8. CONNECTION: DIN POLE
- 9. MOUNTING: FLEXI BASE PLUG IN
- 10. BASE MATERIAL: ABS, EPDM & PVC
- 11. LENS MATERIAL: POLYCARBONATE
- 12. PRODUCT WEIGHT: 0.8Kg (1.76Lbs)

NOTES:

1.DIMENSIONS IN MILLIMETRES[INCHES (FOR REFERENCE]

2.USE SUB ASSEMBLY (100-EB5009A) FOR MANUFACTURE

PROPRIETARY AND CONFIDENTIAL INFORMATION

HIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEBBIN ARE THE PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATE ("PCCC") AND IS SIZED IN CONFIDENCE OR EXPENDING INFORMATION DISCLOSED HEBBIN AND AND INCOME OF THE PROPERTY GROUP AFFILIATE HEBBIN AND NOT BE USED. COPIED, REPRODUCED OR OTHER WISE DISCLOSED IN A PART OR IN WHYCLE TO THEIR OF ARITIS OR USED FOR ANY OTHER PURPOSE WITHOUT PROVING ECCO. REPRODUCTION, USE AND SALES RIGHTS THEREO. THIS DRAWING IS SUBJECT TO RECALL BY ECCO. AT ANY TIME, AND YOUR POSSESSION AND/OR USE CONSTITUTES ACCEPTANCE OF

	SCALE 1:3		APF	ROVALS	DATE						
CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED: D			DRAWN BY NP 2020-01-07			ECCO ° www.eccolink.com					
			CHECKED	LSH	2020-02-03	(XX)					
ſ	TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:			MECH. ENG.	KW	2020-03-10	Americas (800) 635-5900 Europe +44 (0)113 237 5340 Asia Pacific +61 (0)3 63322444				
Ī	MILLIMETERS DECIMALS INCHES DECIMALS ANGLES 0.5°		ELEC. ENG.	MMG	2020-02-03	ECCOLED, SILVER, FLEXI MNT, R65, AMB, 12/24V					
	XX. ± 1.0mm XX.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	FRACTIONS	TEST ENG.	JUP	2020-01-08	CUSTOMER PAR			PRODUCT SERIES:	,
_			± 1/64	SALES.			EB5009	1A		ECCOLED	
S	THIRD ANGLE PROJECTION					SIZE: A4	DWG. NO.	EB500)9A	REV.	
			Electronically Controlled Use Latest Copy		SHEET 1 OF 1	Project: LC1492	Date Cre	Created: 2018-02-08			