	REVISION HISTORY								
REV.	DESCRIPTION	DATE							
Α	INITIAL RELEASE PER LC1492	2018-05-22							
В	REVISED PER LC2114	2019-06-19							
С	REVISED PER LC2445	2020-03-23							

Ø112[4.4]

2- 18 AWG WIRES
_RED - POSITIVE (+)
BLACK - NEGATIVE (-)
CABLE LENGTH APPROX 300mm FROM BOLT

SPECIFICATIONS

1. CERTIFICATIONS: ECE R10

Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise specified, the Product Certifications referred to herein are predicated upon the

Base product model configuration.

- 2. FLASH MODE: 135 ± 15 FLASHES PER MINUTE(DOUBLE FLASH)
- 3. VOLTAGE (NOMINAL): 12/24 VDC
- 4. VOLTAGE (EXTREME): 10 to 36 VDC
- 5. CURRENT (RMS):1.06A (@ 12 VDC NOMINAL)
- 6. CURRENT (PEAK): 1.85A (@ 12VDC NOMINAL)
- 7. POWER (RMS MAXIMUM): 23W (@ 24 VDC NOMINAL)
- 8. TEMPERATURE RANGE: -20°C (-4°F) TO 50°C (122°F)
- 9. CONNECTION: 18 AWG WIRES
- 10. MOUNTING: 1 BOLT MOUNTING
- 11. BASE MATERIAL: ABS & EVA
- 12. LENS MATERIAL: POLYCARBONATE
 13. PRODUCT WEIGHT: 1.32 LBS (0.6 Kg)

150[5.9]	
3:	CABLE EXIT Ø 12[0.5]

NOTES:

1. DIMENSIONS IN MILLIMETRES[INCHES (FOR REFERENCE)]

2. USE SUB ASSEMBLY (100-EB5011A) FOR MANUFACTURE

PROPRIETARY AND CONFIDENTIAL INFORMATION

HIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED BEENER ARE THE PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATE

(*ECO*) AND IS SUED IN CONFIDENCE O' RECPIRENT FOR ENGINEERING INFORMATION PURPOSES ONLY. THIS DOWNING AND THE DESIGN AND OTHER INFORMATION DISCLOSED

WRITTEN CONSENT. ECCO RESERVES ALL PATENT, COPPRIGHT TRADEMARK AND OTHER PROPRIETARY RIGHTS TO THIS DOCUMENT, INCLUDING ALL DESIGN, MANUFACTURING,

REPRODUCTION, USE AND SALES RIGHTS THEREOF, THIS DRAWINGS, SUBJECT TO RECALL BY ECCO, AT ANY TIME, AND YOUR POSSESSION AND/OR USE CONSTITUES ACCEPTANCE OF

SCALE 1:2.5			APP	ROVALS	DATE						
			DRAWN BY	NP	2020-03-05	2020-03-05 ECCO www.eccolink.cor					
DO NOT MANUALLY UPDATE. MODEL REFERENCED: B			CHECKED	LSH	2020-02-03	*					
TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:			MECH. ENG.	FP	2020-03-10	Americas (800) 635-5900 Europe +44 (0)113 237 5340 Asia Pacific +61 (0)3 63322444					
MILLIMETERS DECIMALS	INCHES DECIMALS	ANGLES ± 0.5°	ELEC. ENG.	MMG	2020-02-03	ECCOLED,BRONZE,1BOLT,AMB,12/24V					
XX. ± 1.0mm XX.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	FRACTIONS	TEST ENG.	JUP	2020-02-04	CUSTOMER PAR				PRODUCT SERIES:	
		± 1/64	SALES.		EB5011A				ECCOLED		
THIRD ANGLE PROJECTION						SIZE:	DWG. N	Λ Γ	$D E \cap I$	1 A	REV.
— ——					^{312E.} A4	DIVIG. N	○. E	EB501	IA	KEV.	
		Electronically Controlled Use Latest Copy		SHEET 1 OF 1	Project: L(C1492	Date Cre	eated: 2018-02-05			