

	REVISION HISTORY							
	REV.	DESCRIPTION						
	03	REVISED PER LC1492	2018-05-11					
	Α	INITIAL RELEASE PER LC1492	2018-05-29					
Ī	В	REVISED PER LC2445	2020-05-26					





SPECIFICATIONS

1. CERTIFICATIONS: ECE R10, ECE R65 APPROVED

Note: Unique components, accessories and hardware kits are not typically Included in the product certification test protocols. Unless otherwise Specified, the product certification referred to herein are predicated Upon the base product model configuration.

- 2. FLASH MODE: DOUBLE FLASH PATTERN (135 FPM)
- 3. VOLTAGE (NOMINAL): 12/24 VDC
- 4. VOLTAGE (EXTREME): 10 to 36 VDC
- 5. CURRENT (RMS): 1.06A (@ 12 VDC NOMINAL)
- 6. CURRENT (PEAK): 1.85A (@ 12 VDC NOMINAL)
- 7. POWER (RMS MAXIMUM): 23W (@ 24 VDC NOMINAL)
- 8. TEMPERATURE RANGE: -20°C (-4°F) TO 50°C (122°F)
- 9. CONNECTION: DIN 72591
- 10. MOUNTING: FLEXI POLE
- 11. BASE MATERIAL: ABS & EVA
- 12. LENS MATERIAL: POLYCARBONATE 13. PRODUCT WEIGHT: 0.75KG (1.65lb)

NOTES:

- 1. DIMENSIONS IN MILLIMETRES [INCHES (FOR REFERENCE)]
- 2. USE SUB ASSEMBLY (100-EB5016A) FOR MANUFACTURE

NON DISCLOSURE AGREEMENT

THIS DRAWING AND THE DESIGN IT DISCLOSES ARE THE PRIVATE PROPERTY OF ELECTRONIC CONTROLS CO. AND IS SUBJED IN CONTIDENCE FOR ENGINEERING INFORMATION ONLY. THE DRAWING AND / OR DESIGN MAY HOT BE USED. COPIDE. REPRODUCED, OR DHERWISE DESCRIPED IN PART OR AS A WHOLE TO OUTSDEES OF USED FOR ANY OTHER PURPOSE WITHOUT THE PRIOR WRITTEN CONSENT OF ELECTRONIC CONTROLS CO. THE DRAWING IS SUBJECT TO RECALL AT ANY TIME. YOUR POSSESSION OF THIS DOCUMENT CONSTITUTES ACCEPTANCE OF THESE TERMS. © 20 18 LECTRONIC CONTROLS CO.

l	SCALE 1:2.5			APP	ROVALS	DATE						
	CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED: A			DRAWN BY	NP	2020-05-26			□)	ww.eccolink	.com	
l				CHECKED	LSH	2020-02-03	(XX)					
Ī	TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:			MECH. ENG.	FP	2020-05-26	Americas (800) 635-5900 Europe +44 (0)113 237 5340 Asia Pacific +61 (0)3 63322444					
ĺ	MILLIMETERS DECIMALS	X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	EIMALS ANGLES	ELEC. ENG.	MMG	2020-02-03	ECCO	LED,SILVER,FLEX	I POLE,I	R65,AMB,12/	24V	
l	XX. ± 1.0mm XX.X ± 0.5mm		FRACTIONS	TEST ENG.	JUP	2020-01-09	CUSTOMER PAR			PRODUCT SERIES:		
4			1/04		SALES.			EB5016A			ECCOLED	
1		THIRD ANGLE PROJECTION					SIZE: A4	DWG. NO.	EB50	6A	REV.	
l	7			Electronically Controlled Use Latest Copy		SHEET 1 OF 1	Project: LC1492	Date Cr	eated: 2018-02-12	В		