

**LIGHTBARS** 

**BEACONS** 

**MINIBARS** 

**DIRECTIONALS** 

**WORKLAMPS** 

**SIRENS** 

**SPEAKERS** 

**SWITCHES** 

**AUXILIARY** 



## **GECKO3 Directional LED**



Redtronic's GECKO3 directional LEDs deliver a powerful light output in a slim and compact design. They are part of the GECKO family and are available in 2 sizes including 3 LED (GECKO3) and 6 LED (GECKO6), making them the ideal solution for a wide variety of vehicle applications within the emergency and safety services. The GECKO directional LEDs are available in verticle and horizontal models which are tailored for grille orientation. The GECKO3 comes with multiple mount options which means they can be fitted virtually anywhere on a vehicle in a fit-and-forget fashion. The GECKO3 is available in single colour options and features R65 class I output (amber and blue), EMC/R10 approval IP69K rated including detachable connector (plug and play), CAP168/ICAO approval for airport use, wide angle optics, synchronisation with other units for simultaneous or alternating operation, 6 flash patterns and a 2-year warranty.

Part Number	Colour	Voltage	LEDs	Orientation	Warranty
G3HSAOCB		12VDC	3	Horizontal	2 years
G3HSV0CB		12VDC	3	Horizontal	2 years
G3HSROCB		12VDC	3	Horizontal	2 years
G3HSW0CB		12VDC	3	Horizontal	2 years
G3VSAOCB		12VDC	3	Vertical	2 years
G3VSCOCB		12VDC	3	Vertical	2 years
G3VSROCR		12VDC	3	Vertical	2 years
G3VSWOCB		12VDC	3	Vetical	2 years

## Features and Benefits



- Wide-Angle FX Optics
- Ultra-strong UV stabilised polycarbonate lens
- · Ultra-bright latest generation LED's
- · Colourless when not illuminated
- · R65 class I approved (blue & amber)
- · EMC / R10 compliant
- · CAP168/ICAO airport flash
- IP69K protection against dust & water ingress
- IP69K detachable connector (plug & play)
- · Designed with a Gore-Tex vent for airflow

- · Horizontal and vertical models
- · Multiple mounting options
- · Night & day (dim mode)
- · 6 flash patterns
- · Multiple unit synchronisation
- · Cruise feature available
- · Voltage 12VDC
- · Current draw @12VDC: 500mA
- · Dimensions: L 73.5mm x H 24mm x D 17.6mm
- · Warranty: 2 years





