SL200 Series Scene Lamps



Part# SL200WM SL200LGM SL200DGM SL200BM SL200BGM Voltage Wattage	Description Scene Lamp, White, Retail Box Pack Scene Lamp, Light Grey, Retail Box Pa Scene Lamp, Dark Grey, Retail Box Pack Scene Lamp, Black, Retail Box Pack Scene Lamp, Black/Grey, Retail Box Pa 10-30V 11.5W	9335 ck 9335 ck 9335 ck 9335 9335	Code 5962036639 5962036622 5962036615 5962036608 5962036592	SL200WM SL200UM SL200LGM	2m	1000lx
Dimensions IP rating Warranty Cable Current draw (13.8V / 28V) Raw lumens Effective lumens Lux Colour temperature Operating temperature	200 x 50 x 25mm IP67 3 Years 500mm (stripped-end) 0.84A / 0.40A 1980lm 1050lm 1000lx @ 1m 6500K -35°C to +60°C			SL200DGM SL200DGM	<u>4m</u> 6m	301x
ECE approval	FunctionApproEMC (R10)10R-E9	val# -06-22466		SL200BGM		
Wiring colour codes	RED: Power [+] BLACK: Earth [-]			◄	200	
Mounting instructions	A Installation to be undertaken by Ensure mounting surface is flat, clean of Drill hole for cable, position lamp in de fixings supplied.	and dry prior to installation.			185	50

T: +44 (0)121 313 2222 E: sales@ledautolamps-uk.com LED Autolamps Europe LLP Unit 8J Maybrook Business Park, Minworth, Sutton Coldfield, B76 1AL, UK

www.ledautolamps-uk.com